









Titanengineerings





TABLE OF CONTENTS

ABOUT US	1
COMPLETE DRILLING RIG PACKAGES See our complete line of reliable rig components	2-3
STEALTHWALKER WALKING SYSTEMS	4-5
MAST & SUBSTRUCTURES	6-7
TES DRAWWORKS Drawworks that are efficient to operate and easy to maintain and service	
TES 1600 AC	8
TES 2000 AC	9
TES 1500 EH	10-11
TES 1000 M/MH	12-13
IRON ROUGHNECK The new industry standard	14-15
AIR COMPRESSORS Rotary Screw and Reciprocating	16-17
TORQUE CONVERTERS A wide selection of quality torque converters	18-19
MAN RIDERS AIR HOIST WINCHESComplete line of parts and service	20-21
KELLY SPINNERS	22
PIPE SPINNERS Air and Hydraulic	23
TES EXPLORER SERIES WIRELINE MACHINES Electric over hydraulic units	24
MUD AGITATORS CENTRIFUGAL PUMPS SHALE SHAKERS	25
SERVICES CNC & MANUAL MACHINE SHOP	26

Titan Engineering Supplies offers outright and exchange units, parts and





ABOUT US

Titan Engineering Supplies has been active in the oil and natural gas drilling industry for over 25 years. During this time, TES has grown from a small repair shop to a full-service drilling rig equipment manufacturer. TES manufactures and rebuilds multiple lines of equipment not limited to:

- Substructures
- Mast
- Rig Walking Systems
- Iron Roughnecks

- Drawworks
- Torque Converters
- Air and Gas Compressors
- Air Hoists

- Winches
- Kelly Spinners
- Pipe Spinners
- Wireline Machines

Titan Engineering Supplies ("TES") was founded in 1991 by Johnny Kidd, Kenny Black, and Tom Luttrell. HQ in Odessa, TX has functioned as a full-scale manufacturing API facility since 2015.

The majority of Company sales come from replacement components — replacing, refurbishing, and/or upgrading worn, ineffective, or outdated equipment on existing rigs. TES also sells component and full rig packages, primarily to drilling contractors looking to grow their fleet. TES sells and services individual components and can sell, service, and assemble an entire drilling rig on site.

TES operates from an approximately 30-acre campus that includes 20 buildings with ~126,000 square feet of gross building area.



TES knows how costly rig downtime can be to an operation. Our 25 plus year history of serving the oil and gas industry has revolved around providing products and services to maximize drilling efficiency and well production, while minimizing downtime.

We manufacture a complete line of reliable rig components from our Odessa, TX facility, which can be customized to meet the specific needs of our customers. In addition, our repair and exchange program ensures that customers receive the necessary products quickly.



AC & DC DRILLING RIG PACKAGES

The TES IRONMAN Rig Package is a complete package consisting of an TES AC Drawworks, with Independent Rotary Drive, Top Drive, Mud Pumps, Pit System, Substructure and Mast, Walking System, Caterpillar Power Systems and can include any combination of support equipment the customer desires. The AC and DC Rig Packages are built in accordance with IADC & API specifications. All new Rig Packages include a one year warranty with full mechanical & electrical rig up and on site commissioning.

As a design build facility, we can equip your rig to your precise requirements. To learn more about how we can customize an AC/DC rig to your exact specifications, please call us at 1-432-381-5265.



TES STEALTHWALKER RIG WALKING SYSTEM

Total lift capacity of 3,000,000 lbs Stealth Pods have a 600,000 lbs. to 750,000lbs per corner rating each at 3000 PSI Move the rig in 8 directions up to 60 feet per hour












SUBSTRUCTURES

Titan Engineering Supplies, is a leading innovator of substructures in the rig arena. Our company has been in the Oil & Gas drilling equipment business for over 25 years, supplying new and refurbished substructures to customers all over the world.

Our self-elevating or box on box substructures are designed to support all needed components and also provide additional storage in the lower sections of the substructure. They can be customized for specific rig packages with a high degree of adaptability for varying ground conditions and well types including the use of rig mats.





- Set of (4) Stealth Pods that can be pinned to the end of the substructures
- Stealth Pods Integral to Pony Subs
- Total lift capacity of 3,000,000 lbs.
- Stealth Pods have a 750,000 lbs. rating each at 3000 PSI
- Move the rig in 8 directions at up to 60 feet per hour
- Move rig 24" per cycle











- Hydraulic Power Unit with
 - (2) 75 HP electric motors and starters
 - 3000 PSI continuous operating capability
 - Self-contained skid with 200 gallon reservoir
 - Electric pump for filtering tank filling
- Wireless Remote Operator
- Includes installation at TES facility
- Manufactured in accordance with API Q1 QMS and designed to meet API 4F











SUBSTRUCTURES



- Analysis for load rating and set back capacities
- Perform API CAT III and CAT IV inspections and repairs
- Substructure modifications to increase rig floor height and rotary loads
- Modify set back area to increase load capacities and racking capacities
- Installation of drawworks / rotary table / iron roughneck socket and all additional flooring needs
- Design, build and installation of outriggers as per customer requirements
- Upgrades or modifications needed to mud lines as per customer requirements
- Upgrades or modifications needed to deadline anchors
- BOP trolley rail systems
- Sandblast and paint to customer specifications
- Field service and repair when applicable



The TES 1600 AC integrates some of the latest technology and safety features available today with the durability and familiarity of units that have been designed and built for years. Our goals were to design and build Drawworks that were efficient to operate and easy to maintain and service.

NOTABLE FEATURES:

- A/C Gear Drive Drawworks
- Maximum Hoisting Capacity 750,000 Lbs on 10 Lines
- Drum Diameter 31"
- Drum Length 54-1/4"
- · Single Speed Gear Box with 9.907 Ratio
- Optional Two Speed Gear Box

- External Lube System with Heat Exchanger and Filter
- · Heavy Duty Frame and Skid
- A/C Drilling Motor with Drawworks Rating of 2250 HP
- Spring Set, Pneumatic Release Parking Brake
- Dynamic A/C Motor Braking






The TES 2000 AC integrates some of the latest technology and safety features available today with the durability and familiarity of units that have been designed and built for years. Our goals were to design and build Drawworks that were efficient to operate and easy to maintain and service.

NOTABLE FEATURES:

- A/C Gear Drive Drawworks.
- Maximum Hoisting Capacity 860,000 Lbs on 10 Lines.
- Drum Diameter 31".
- Drum Length 54-1/4".
- Single Speed Gear Box with 9.907 Ratio.

- · Optional Two Speed Gear Box.
- External Lube System with Heat Exchanger and Filter.
- · Heavy Duty Frame and Skid.
- A/C Drilling Motor with Drawworks Rating of 2700 HP.
- Spring Set, Pneumatic Release Parking Brake.
- Dynamic A/C Motor Braking.







TES 1500 EH

The TES 1500 EH integrates some of the latest technology and safety features available today with the durability and familiarity of units that have been designed and built for years. Our goals were to design and build Drawworks that were efficient to operate and easy to maintain and service.

HYDRAULIC FEATURES:

- Hydraulic Catheads controlled by Hawe joystick, adjustable at console
- Hydraulic winches controlled by Hawe joystick
- Winches operated at console or by remote control with safety lockout
- · Remote has E stop and keyed lockout
- E stop on panel

HYDRAULIC POWER UNIT:

- Start/stop on panel
- Integral to master skid
- 50 hp 41 gpm, 2300 psi pressure compensated
- Piston pump











NOTABLE FEATURES:

RATING:

- •1500/2000 Input Horsepower
- 90,000 lb. Single Line Pull

DRAWWORKS:

- (2) Joliet 752 Electric Motors Mounted to Input Shaft
- · Rotary Back Brake
- 46 X 10 Low Drum Clutch
- 40 X 10 High Drum Clutch
- 28 X 5 1/4 Rotary Clutch
- 50 X 10 Brake Rims
- Drum Grooving 1 3/8"
- 27 X 49 Drum Core
- EATON Water Cooled 336 WCBD Brake Includes:
 - -Stand Alone Trip and Drill System
 - -On/Off on Drillers Side
 - -25%-75%-100% Selector on Drillers Side
 - -Control Cabinet Uses Standard Valves
 - -Optional Eddy Current Auxiliary Brake

SKID FABRICATION:

- Materials chosen to maximize vertical strength and minimize weight
- Master skid is fabricated from 18" 71 lb. beam
- Engine skid is fabricated from 10" 45 lb. beam

SERVICE FEATURES:

- Valves can be removed from outside, or complete panel is removable
- Equalizer beam and pin plates have replaceable aluminum bronze bushings
- EATON brake is removable or serviceable without disassembling cradle (outboard mounted)





TES 1000 M/MH

The TES 1000 M/MH integrates some of the latest technology and safety features available today with the durability and familiarity of units that have been designed and built for years. Our goals were to design and build Drawworks that were efficient to operate and easy to maintain and service.

NOTABLE FEATURES:

RATING:

- 1000 input horsepower
- 52,000 lb. single line pull

DRAWWORKS:

- · Drum shaft diameter 8 in.
- 6 Speed transmission
- · Large capacity bearings throughout
- Straight roller bearings and ball thrust bearing in low floating sprocket.
- EATON 236WCBD water cooled brake
- 32VC1000 low drum clutch
- 28VC650 high drum clutch
- · 24E475 rotary clutch
- · Rotary back brake optional
- · Inertia brake
- · Control cabinet uses standard valves
- Spacers and shoulders between bearings to eliminate sprocket damage during gear shifts
- EATON brake has stand alone trip and drill system, on/off on drill side and 25%–75%–100% selector on drill side

SKID FABRICATION:

- Materials chosen to maximize vertical strength and minimize weight
- · Master skid is fabricated from 18" 71 lb. beam
- Engine skid is fabricated from 10" 45 lb. beam

COMPOUND:

- Accommodates 17" or optional 22" Engine centerlines
- · One piece fabricated housing
- · Internal supports and gussets
- · Belt-driven compressor optional







SERVICE FEATURES:

- · Valves can be removed from outside, or complete panel is removable
- Brake pedestals have replaceable aluminum bronze bushings.
- Equalizer beam and pin plates have replaceable aluminum bronze bushings
- · EATON brake is removable or serviceable without disassembling cradle (outboard mounted).
- Air clutches can be replaced or repaired without removing shafts
 Example: low drum, high drum, EATON brake, engine clutch, back brake (exception rotary clutch)
 Removable siphon pipe / water box adapter inside drum shaft.

HYDRAULIC FEATURES:

- Hydraulic Catheads controlled by Hawe joystick, adjustable at console
- Hydraulic winches controlled by Hawe joystick
- Winches operated at console or by remote control with safety lockout
- · Remote has E stop and keyed lockout
- · E stop on panel

HYDRAULIC POWER UNIT:

- · Start/stop on panel
- · Integral to master skid
- 50 hp 41 gpm, 2300 psi pressure compensated
- Piston pump




IRON ROUGHNECK PARTS AND SERVICE

The Iron Roughneck is the new industry standard. Modern rigs are being built better, safer, and more accurate, the Iron Roughneck will be safer and more accurate than those past. Iron Roughneck's are great equipment, but it can be too expensive to own a replacement.

In certain cases we offer an exchange program for clients, eliminating the repair/maintenance process completely. We come on-site, replace, and later repair here at our shop for later use. Titan Engineering Supplies, the next generation oilfield technology built and serviced right here in Odessa, TX.

In addition to service and repair, we also provide complete overhauls and rebuilds of the Iron Roughnecks. Additionally, we perform upgrades to increase efficiency in operation. This significantly increases the life span of the Iron Roughnecks, increasing the operating cycle of the equipment.







AIR COMPRESSORS





SULLIVAN PALATEK ROTARY SCREW AIR COMPRESSORS

Titan Engineering Supplies offers service and repair on all makes and models, and is your authorized distributor for Sullivan Palatek Rotary Screw Air Compressors.

STANDARD FEATURES

15, 20, 25, 30 & 40 hp Air Compressors

COMPRESSOR: Oil flooded rotary screw, continuous duty, industrial air compressor. Five-year air end warranty.

ELECTRIC MOTOR: 200-208-230-460 volt, hi-efficient Nema T-frame, C-face, design-B with class-F insulation and B temperature rise. Open drip proof type enclosure. Five-year warranty.

MOTOR STARTER: 230/460 volt (15-30 hp) 460 volt (40 hp), full voltage magnetic starter with 110 volt controls, Nema 1 enclosure, solid state circuit breaker protection for controls, and three-phase overload protection with manual reset.

COUPLING & DRIVE: Compressor is flange mounted to motor C-face for positive alignment and direct driven by zero maintenance coupling which carries a five-year warranty.

AIR INTAKE FILTER: Two stage heavy duty dry type with replaceable element.

SEPARATOR TANK: ASME coded 200 PSIG sump tank, minimum pressure/check valve, relief valve, high efficiency replaceable oil separator element, fluid level sight indicator, and vented fill cap.

COOLING SYSTEM: Air cooled with air cooled aftercooler, spin on oil filter and factory filled with Palasyn 45 synthetic lubricoolant.

CONTROLS: Full modulation, solenoid controlled for smooth lowest possible no load power. Automatic start/stop or constant speed timed dual control.

INSTRUMENTATION: Air pressure gauge, hour meter, and discharge temperature gauge.

PROTECTIVE DEVICES: Class 20 overload relay, high temperature and overpressure shutdown switches, anti-restart pressure switch preventing starting while air compressor is pressurized and anti-reversing feature.

MOUNTING: Base mounted, platform or tank mounting optional. No special foundation required.

GENERAL: Consult factory for options or accessories not listed. Specifications subject to change without notice.



GARDNER DENVER AIR COMPRESSORS



QUINCY AIR COMPRESSORS VACCUUM COMPRESSORS

Service and Repair Offered 24/7

Titan Engineering Supplies offers outright and exchange units, parts and service.

Complete units, assemblies, and parts are normally in stock and ready for same day shipping.



TORQUE CONVERTERS

0



TES TORQUE CONVERTERS

Units are available for:

- Drilling power (floor motors)
- Pump drives
- Cranes
- Draglines
- Mining equipment



NATIONAL TORQUE CONVERTERS

Units are available for:

- Drilling power (floor motors)
- Pump drives
- Cranes
- Draglines
- Mining equipment



TWIN DISC TORQUE CONVERTERS

Series:

Torque Converter

10000

11500 13800 16000

4SD

Fluid Coupling 27 HUD-00



ALLISON TORQUE CONVERTERS

Series: Units are available for:


TC800

- Pump drives
- Crane
- Draglines
- Mining equipment



Service and Repair Offered 24/7

Titan Engineering Supplies offers outright and exchange units, parts and service. Complete units, assemblies,





AIR HOIST/ WINCHES

Titan Engineering Supplies, offers full service on any brand or make of air hoist. Our company offers a complete line of parts and service for Ingersoll-Rand air winches and Manrider units. New and remanufactured units are available for exchange or outright sale.

Titan Engineering Supplies offers Winches and Hoist for:

- Drilling Rigs
- Floors and Subs
- Drill Line Spoolers
- Derrick/Mule Winch
- Mining Industry
- Manlifting Applications
- General Construction



ODEL TES 1500 KELLY SPINNER

on the market are single speed (wide open). They are engaged by Pneumatic Kelly Spinners currently opening a valve that can only supply full air flow to the motors on the Kelly Spinner which means they can only ted at full speed (approximately 150-200 rpm, depending on load) when making-up or breaking-out pipe.

The TES 1500 includes a Pilot Operated Pressure Control Valve & Throttle Control Actuator Valve which gives the operator full control over the speed range (rpm) of the Kelly Spinner from 1-200 rpm. This is a huge safety factor in the operation of these units.

Pneumatic Kelly Spinners currently on the market use a Vane type air notor. This type motor requires a surge of air to start its rotation and must maintain a certain speed to continue rotating. The air use for these Kelly Spinners @ 120 psi. is approximately 600 scfm and produces approximately 25 hp and 93 ft-lbs torque. The Vane type motor also requires treated air that must go through a lubricator and water filter to clean the air supply before it enters the motors.

The TES 1500 utilizes a Turbine motor which will operate efficiently from 1-200 rum stem speed. The Turbine motor requires no lubrication and uses only a "Y" strainer to keep large debris out of the motor. The air use for the TES 1500 @ 120 psi, is approximately 475 scfm and produces approximately 37 to and 105 ft-lb torque.

The TES 1500 utilizes a Turbine motor which will operate efficiently from 1-200 km stem speed. The Turbine motor requires no lubrication and uses only a "Y" strainer to keep large debris out of the motor. The air use for the TES 1500 @ 120 psi. is approximately 475 scfm and produces approximately 37 hp and 105 ft-lb torque.

Pneumatic Kelly Spinners currently on the market use a bearing arrangement that includes a tapered cup and cone in a rop bearing carrier and a tapered cup and cone in a bottom bearing carrier. This arrangement allows the Kelly Spinner Stem to move inside the housing when the pipe is being torqued which results in wear on the stem and labyrinth plates. This arrangement also allows for excessive bearing clearance and in some cases premature failure.

The TES 1500 has a full tapered roller bearing set in the top bearing carrier and a straight radial roller bearing in the bottom bearing carrier. This gives much more stability to the Kelly Spinner Stem when the pipe is being forged and eliminates premature wear to the stem, labyrinth plates, and bearings

TITAN ENGINEERING SUPPLIES

has been in the repair and manufacturing business for over 25 years. During this time we have repaired many Preumatic Kelly Spinners and in most cases have found the same failures and safety issues. We have addressed this problem and believe our new TES 1500 Pneumatic Kelly Spinner to be the best on the market. We offer variable speed control, increased torque through its entire rpm range, increased safety, and to maintenance











HEIGHT: WEIGHT:

WEIGHT: 720 LBS

PIPE SIZE RANGE: 3-1/2" drill pipe through 7.0" drill collars


AIR REQUIRED 240 cfm @ 100 psi

MODEL TES 35C-7 PERFORMANCE							
Size	3-1/2"	4"	4-1/2"	5"	5-1/2"	₹ 7"	
TORQUE FT:/LB.	810	930	1040	1160	1270	1620	
R.P.M.	170	150	134	120	110	85	

Torque@ 100psi @240cfm No chain slip RPM at above torques

TES 35C

CREASE Titan Engineering Supposed factures the TES 35C7 Pipe Spinner at our facilities in Octoffer new and rebuilt unlassed a full line of replacement parts and assemblies.





MUD AGITATORS

The TES Pit Boss is available in a range from 5-20 hp. These units are lightweight and compact to allow for quick and easy installation. The gear box and electric motor come preassembled and base mounted. The bases are powder coated to guarantee long life and minimize corrosion. Service is available on all brands.



CENTRIFUGAL PUMPS

Titan Engineering Supplies offers service from minor repairs to complete overhauls on centrifugal pumps. We also stock parts and complete remanufactured units at our warehouse in Odessa, Texas.



SHALE SHAKERS

Titan Engineering Supplies rebuilds all makes and models of shale shakers or can custom build new units to customer specifications.





QUALITY CONTROL, DESIGN, REVERSE ENGINEERING & ENGINEERING

To assure optimum quality standards, Titan Engineering Supplies utilizes computer assisted drafting and drawing file maintenance on our production items. We have quality control procedures in place for monitoring and recording all steps of our manufacturing process. Specific tooling includes: machine leveled granite inspection tables with height gauges and digital coordinate measuring equipment.

- · Manual Lathes:
- Max
- Turning 74" O.D. 14' Length
- · Manual Mills:
- Travel capacities
- Table Travel 116"
- Saddle Travel 98"
- Column Travel 66"
- Shaping
- 48" Diam
- Gear & Sprocket Hobbing 36" Diam
- Drilling
- 6" Diam
- CNC Lathes:
 - Turning capacities up to 40" X 50"

- · CNC Machining Center "Mill":
- Travel capacities
- 50""X" Travel
- 20""Y" Travel
- 20""Z"Travel
- Computerized Balancing
- Waterjet Cutting
- Engine Lathes
- Vertical Boring Mill
- Horizontal Boring Mill
- Gear Hobb
- Vertical Shaper
- Drill Press
- Horizontal Saw





